

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 May 2001 (10.05.2001)

PCT

(10) International Publication Number
WO 01/33429 A2

- (51) International Patent Classification⁷: **G06F 17/30**
- (21) International Application Number: **PCT/US00/29516**
- (22) International Filing Date: **27 October 2000 (27.10.2000)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
60/162,333 29 October 1999 (29.10.1999) US
09/691,322 18 October 2000 (18.10.2000) US
- (71) Applicant: **GRAVITATE, INC.** [US/US]; 167 Hamilton Ave., Palo Alto, CA 94301 (US).
- (72) Inventor: **TANAKA, Hirohisa, A.**; 350 Sharon Park Drive, Apartment 24 G, Menlo Park, CA 94025 (US).
- (74) Agents: **WRIGHT, Bradley, C. et al.**; Banner & Witcoff, Ltd., 1001 G Street, N.W., Eleventh Floor, Washington, DC 20001-4597 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— *Without international search report and to be republished upon receipt of that report.*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: **METHOD FOR PROVIDING MATCHING AND INTRODUCTION SERVICES TO PROXIMATE MOBILE USERS AND SERVICE PROVIDERS**

(57) Abstract: A system enabling mobile wireless users to obtain information on other proximate users both fixed and wireless. Said information is gathered from a central database that stores user profiles and real-time locations of system users. Mobile users can request information on nearby users by submitting a request from a mobile telephone or similar communications endpoint to the central database. The request is accompanied by the user's location, obtained from GPS (Global Positioning System) or other technology, or from user input. The server searches the profile database for nearby users based on requester's location, locations of other users of the system and optional parameters specified in the request. Search results are returned to the requester. The system facilitates communication between requester and owner(s) of profiles returned by system.

WO 01/33429 A2

**METHOD FOR PROVIDING MATCHING AND INTRODUCTION
SERVICES TO PROXIMATE MOBILE USERS AND SERVICE PROVIDERS**

5 **CROSS-REFERENCE TO RELATED APPLICATION**

This application claims the benefit of the filing date of the previously filed United States Provisional Application Serial No. 60/162,333 filed October 29, 1999, as provided under 35 U.S.C. 119(e).

10 **TECHNICAL FIELD**

The present invention relates in general to a personal matching/meeting service that utilizes wireless, and/or Internet infrastructures coupled with real-time positional data. Said infrastructures are used to connect users to a database of user profiles and real-time positional data. Said database is used to inform system users
15 when they come within range of other users who meet search criteria. In particular, the present invention relates to improving personal meeting/matching services by locating users using positioning technology embedded within the wireless communications unit, peripherally attached, manually entered or obtained from the mobile communications infrastructure.

20 **BACKGROUND ART**

Several Internet based technologies have sought to introduce people and facilitate forms of dialogue. One such technology is the "chat room". In its traditional form, a chat room allows users to type messages via a keyboard and to view in real-
25 time the messages that are typed by themselves and other users. Another technology known as a "news group" allows users to post messages, data, and post replies to posted messages. In both of these technologies, the users in a given chat room or on given news groups are physically separated, often by thousands of miles. Neither the chat room nor the news group allows the user to gather information about people
30 around him, or to search for people around him.

Another more traditional system for introducing people is the dating or personal matching service. The object of such a system is ultimately to arrange a face-to-face meeting. In traditional systems, users submit a profile to the system

containing information about them and about whom they would like to meet. The problem with traditional personal matching systems is that they do not maintain the user's real-time positions. This means that the system will probably only provide matches to users who live near each other. A dating service that matched a person in New York with a person in Moscow would be useless to most users despite the fact that the person in Moscow might well provide the best compatibility with the person in New York. The problem is that the parties are too physically distant for a meeting to be practical. However, if the New Yorker ever found himself in Moscow, a meeting would be feasible, but the traditional matching system would be unaware that the users had come within reasonable range of each other, because traditional systems do not maintain the real-time positions of the users. Thus the traditional system would not arrange for the parties to meet. A more detailed description of the need for the invention disclosed herein is found in United States Provisional application Serial No. 60/162,333 filed October 29, 1999 and is hereby incorporated by reference.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a system level schematic.

FIGURE 2 illustrates one embodiment of a plurality of user profiles stored within the Secure Real-Time Positional database of Figure 1.

FIGURE 3 illustrates a typical message timeline of the system of figure 1.

FIGURE 4 is a flowchart embodiment of the present invention for searching the Secure Real-Time Positional database of Figure 1.

DISCLOSURE OF THE INVENTION

An object of the invention is to provide matching and /or introduction services between mobile users, and other mobile users or non-mobile users, in response to real-time, proximate positioning and correlated user profiles.

Users establish profiles in a central secure real-time positional (SRTP) database via WWW technology. Said profiles contain personal information the user chooses to reveal. Individuals or service providers, such as a restaurant or a taxi service (mobile or fixed locations) can establish profiles. This information may include hobbies, interests, gender information, age, etc. Profiles are based on a

standard format, but users have the option of customizing content. Users choose which portions of their profile to make accessible, when, and to whom, via a user customizable "PublicImage" which follows permissions similar to UNIX-based file permissions. Users define Access-groups and assign Access-control permissions to those groups for various sections of the PublicImage similar to the UNIX operating system method for access control for file and directory structure read/write privileges. The system contains a security flag, which can be set by the user to prevent his PublicImage from being viewed by other users of the system. For example, a user might create a group called "Friends" and a group called "Business Associates." The Friends group might be given read permissions to the user's hobbies list, while the Business Associates group would not. The Business Associates group might be given read permissions to schedule and resume information, whereas friends may not be given access to this data. Users may update or alter their profiles with their mobile unit (MU) or other communications terminal, fixed or mobile. Each user, is assigned a *user_ID* which is a string of characters used to uniquely identify the owner of the PublicImage. The *user_ID* is conceptually similar to the UNIX user/login name.

Essential to the functionality of the system is the real-time position of the users, and the exact date and time the position is logged. The user's position and "registration time" is stored in the SRTP database with the user profiles. The registration time could be obtained from an operating system call made by the server to determine the exact date and time the server receives the user's position, or the user's message (with position information) could be date and time "stamped" by the MU immediately prior to transmission.

Mobile users move about with mobile communication units in their possession. Said mobile units are capable of establishing data connections via a wireless link, through a wireless infrastructure, to the Internet, and ultimately to a server that communicates with the SRTP database. Said mobile units contain a means for determining and relaying the geographic position of the mobile unit to the server. Said means for determining the position of a MU might be an integrated GPS receiver, cellular triangulation such as Time Difference of Arrival (TDOA), LORAN system, or even a more coarse position determination technique such as using the closest broadcasting base-station based on Received Signal Strength Indication (RSSI) or other means. Ideally, the position sensor would be a GPS receiver

embedded in (or attached peripherally) to the mobile unit (or users mobile laptop computer), but the positional sensor (or data source) could also be the user himself. In this case, the user could manually enter his position into the mobile unit, either by typing on a keypad or keyboard, or by using a stylus and tapping a map or location in a table. The most likely format for user entered data would be street address or other physical landmark (e.g. Fenway Park in Boston Mass.). An element of this invention is the mechanics of *tapping* (or otherwise contacting) on a map (or table/spreadsheet entry, computer icon etc.) displayed on a computer screen resulting in the automatic relaying of the users current geographic position to the SRTP database. This is similar to the "*click and buy*" feature currently employed on the Internet for purchasing a product or service where a computer mouse is used to "click" on a computer icon. The system is not restricted to a single position data format (e.g. latitude and longitude used for GPS or LORAN coordinates). The server (or other system component) would simply identify the format and translate it into a data format used within the database.

A server is typically used to provide access to the SRTP database. One implementation of the server is an HTTP server. The purpose of the HTTP server is to facilitate an HTTP transport layer connection with the mobile unit or intermediate point. Said connection allows the user to update his portion of the database. In a typical implementation, the HTTP server would generate WWW pages that would be viewed from any WWW browser. Said WWW pages contain forms that would allow the user to be authenticated by the HTTP server, edit his PublicImage, edit his Access Control, edit his Access groups, submit search requests, etc. Said HTTP server is also used to return results of database queries to the user in browsable form.

Once users have registered their profiles with the system, they can use their MU to update their position and submit queries of the database and be notified of queries made by other users. Mobile user records exist in the database in one of the following states:

Locked: Users in locked mode will not be included in searches from other users. Users can set themselves in locked mode for privacy or security reasons. If the user's position has not been updated after a predetermined time set by the user, the position is considered invalid, i.e. timed out. Unless the user takes steps to update the position data, he or she will not be included in any query_results from other users. Non-mobile users, such as fixed-point service providers can set time-out to infinity,

meaning that their position will not change. An optional operational feature may be the users position can be updated autonomously simply by the user setting an auto_position flag. When the auto_position flag is set, the MU transmits the user's geographic position to the server every time the MU unit registers with the local
5 wireless cell/PCS site in the same way a cellular phone performs auto registration, already well known in the art of wireless communications.

Standby: The user goes from disconnected to standby by registering his current location to the server. In standby mode user profiles become accessible to server queries and time-out counters are set.

10 Browsing mode: In browsing mode, the user submits a request to the server. The request contains search parameters the database server uses to find matching profiles, as well as the position of the requester. By obtaining the location of the requester, the database can return profiles for users that are physically close to the requester. "Near" is a user defined search radius accompanying the request or as part
15 of the user profile.

In addition to position, search parameters and search radius, the user can specify temporal parameters for the search(s) to occur. One temporal parameter, periodicity, allows a user to tell the server how often to perform the defined search, for example every 30 minutes. The user can also specify the persistence of the search.
20 The persistence determines the number of searches that are to be carried out. The user can define the persistence as a number of searches, or as a maximum time interval to continue searches. For example, perform 24 searches, or search for the next 12 hours.

Combining periodicity and persistence in the example *supra* yields "search every half hour for the next 12 hours."

25 Once a user has submitted a request, he or she receives a reply from the server containing accessible portions of PublicImages of other users matching the requesters query. The user reviews the search results via the MU and interacts with the search results much in the same way WWW users interact with results from search engines. The user views the PublicImages and decides whether or not to request to contact the
30 owner of a specific PublicImage. The request to contact the owner of a Public Image is initiated by sending the requester's (Person A) PublicImage to the desired recipient (Person B). If Person B is not a member of any access control group previously defined by Person A, Person B accesses Person A's PublicImage with "Public" access

permissions, containing the most limited information from Person A's Public Image. Included in this request for contact is a list of preferred means of contacting Person A. Person B can choose to accept or reject the request for contact from Person A. If Person B chooses to accept the request, Person B must choose a method of responding. The system supports secure contact, in which no personal contact information is disclosed. For example, an email message can be sent through the server without revealing either person's private email address or location. Contact can also be initiated through Caller-ID blocked phone calls or any other means. Consequently, Person A and Person B can choose to initiate face-to-face contact.

Figure 3 describes an embodiment of message traffic between a mobile terminal and the SRTP database. The nature of the transport layer connections is not shown on the diagram, but are well known in the art. In one embodiment the MU would be connected to the WAP (Wireless Application Protocol) server via a WAP connection and the WAP server would be connected to the HTTP (WWW) server via an HTTP connection.

The purpose of the user initiated search request, *search_req*, is to allow the user of a mobile unit to query the WWW server to perform a database search. Search criteria are contained within the message body. For example, the message might instruct the web server to search the SRTP database for profiles including the word "baseball". It could further instruct the web server to return profiles only for users within a given geometric radius, for example 2 miles from the user. The *search_req* of this embodiment has 5 fields: requestor_ID, password, user position, search_words, and search_radius. These fields could either be encoded or sent as cleartext. The following *search_req* fragment assumes the *search_req* is sent as cleartext. In this embodiment the keywords and values are sent as colon separated pairs.

```
search_req = "requestor_ID:John23:password:xdw94f4:position:GPS 234.33  
153.65:search_words:baseball:search_radius:1 mile"
```

The *search_req* becomes a *dbase_query* after being forwarded to the Secure Real Time Database by the server (e.g. WWW server). Said query is formulated based on the *position*, *Search_radius* and *search_words* fields in the *search_req*.

The *requestor_ID* (or *user_ID*) field in the *search_req* divulges to the WWW server the identity of the registered system user who is making the request. The *password* is used for security to insure that the request in fact originated from the user who originally registered with the WWW server.

- 5 The *position* field in the *search_req* is used to convey the requesting users geographic position to the web server. The value following the position field (also referred to as a key) includes information that identifies what type of positional data is being presented. If the mobile unit has an integrated (or peripherally attached) GPS unit, the mobile unit would send GPS coordinates as the standard latitude and
10 longitude. Other formats are also supported. For example, users without GPS receivers might need to enter the position manually as a street address. In this case the position key:value pair might appear as "position:STREET 345 main St., anytown, anystate, USA". Furthermore, if this data were provided by the cellular infrastructure itself through triangulation of radio signals using Time Difference of Arrival (TDOA)
15 or some other location technique, the position field would originate within the mobile communications infrastructure.

- Some key:value pairs are optional. For example, if no search words were sent, the WWW server would have default search capability that uses search words from the requester's user profile as *search_words*. The *search_radius* could also be omitted
20 and the WWW server would perform the database search using a default radius (e.g. one mile). The password might also be omitted if some information such as the MU's Mobile Identification Number and/or Electronic Serial Number could be automatically obtained from the phone or mobile communications infrastructure to verify the identity of the requesting MU.

- 25 The Secure Real Time Position database (SRTP) yields raw, unformatted data, *database_query_results*, that are the results of the database query and are returned to the server. The WWW server reformats the *dbase_query_results* and returns the data to the user in a browsable form as *query_results*.

30 **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT**

 With reference to Figure 1 of the drawings, a system 10 for providing a method of matching and introduction services generally includes position determining means 1, a communications device 2, which may be fixed or mobile, a wireless

communications infrastructure 3, an Internet connection 4 that may be wired or wireless, a server 5 provides access to Secure Real Time Positional (SRTP) database 6. Referring to Figure 2, the SRTP database 6 includes a plurality of user profiles 7, 8, and 9.

5 With reference to both Figures 1 and 2, a first user creates a *user_profile* 7 using a communications device 2 which is preferably a wireless mobile phone, wireless Personnel Digital Assistant (PDA), beeper, or additionally a fixed terminal, wired or wireless, and stores said *user_profile* 7 in the Secure Real Time Positional database 6. Said *user_profile* 7 comprises a *user_ID*, user password, said first users
10 current geographic position, the time and/or date said first users current position was last updated, a security lock to prevent viewing of said *user_profile* 7 by other users, access control features to assign read/write privileges to other users or groups of users, and a *PublicImage* portion of said *user_profile* 7 which said first user customizes with any desirable content such as hobbies, dating preferences, music
15 preferences, or even graphics, audio, video, or text.

Said SRTP database 6 contains a plurality of previously registered additional *user_profiles* 8, 9 each also comprising a *user_ID*, user password, users current position, the time and/or date a users current position was last updated, a security lock, access control features, and a *PublicImage* portion of said *user_profiles* 8,9.

20 Said first user submits a *search_request* to the system 10 using communications device 2 together with search criterion including keywords and geographic search radius. Said first user's geographic position is automatically determined by position sensor 1 and is embedded in the *search_request* submitted to the system 10. Position sensor 1 is preferably an embedded Global Positioning
25 System (GPS) receiver or "chipset" integrated into the communications device. An alternate embodiment is a display 11 in the communications device 2 that presents said first user with information such as a map so said first user may simply tap the display 11 in the communications device 2 with a stylus or other pencil-like instrument at the location where said first user currently resides. The communications
30 device 2 recognizes the precise geographic location of the user by where on the display 11 said first user taps and automatically includes this location in the *search_request* submitted to the system 10. The techniques whereas a computer can correlate a tap on a display with data in the computers memory is already well known

in the art such as is used in the Hewlett Packard 360LX palmtop PC. The novelty in the invention disclosed herein is that the tap on the display 11 is interpreted as a geographic position by the communications device 2 and is automatically relayed to a distant location, in this embodiment, the server 5. The information presented on display 11 can be a map, table of landmarks, list of streets, or even an address corresponding to a phone number such as the E911 services employ.

Said first users *search_request* is transmitted by the communications device 2 to the wireless communications infrastructure 3 where a connection is made to the Internet 4. The connection to the Internet 4 may alternately be made through an optional intermediate Wireless Application Protocol server 12 to facilitate communications as shown in Figure 1. Said first user's *search_request* arrives at the World Wide Web (WWW) server 5 from the Internet 4.

Referring to Figure 4, said first users *search_request* is authenticated and parsed for the required information and syntax by server 5. The server 5 then updates said first users geographic position in the SRTP database 6. The server 5 begins the search process for a match or matches to said first users *search_request* by first querying the SRTP database 6 for other users that are geographically proximate to said first user within the search radius specified in said first users *search_request* or said first users *user_profile* if a search radius is not included in said first users *search_request*. Other user_profiles 8,9 returned from the SRTP database 6 are then searched by the server 5 for search_words specified in said first users *search_request* or said first users *user_profile* if search_words are not included in said first users *search_request*. The user_profiles 8,9 that are both geographically close to said first user and contain some of the search_words specified by said first user, are examined for access control restrictions specified in said user_profiles 8,9. The PublicImages of the user_profiles 8,9 that do not have any access control features enabled are relayed to said first user as *query_results*. Said first user examines *query_results* returned by system 10 for user_profiles that are of interest. Said first user chooses a user_profile 9 belonging to a second user. The system 10 responds to said first users selection of user_profile 9 by notifying said second user that said first user wishes to make contact in the manner specified by said first users *user_profile* 7.

Throughout this specification, reference is made to mobile units and mobile communications infrastructure. A mobile unit is a mobile computing or

communications device, including for example a cellular phone with web browser, a PDA with wireless connectivity, a laptop with CDPD modem, and the like. Mobile communications infrastructure is the infrastructure that provides the wireless connectivity to the mobile unit. A typical implementation would be a cellular
5 communications infrastructure comprising cellular base stations and mobile switching centers. Other implementations are possible.

In accordance with the provisions of the patent statutes and jurisprudence, exemplary configurations described above are considered to represent a preferred embodiment of the invention. However, it should be noted that the invention can be
10 practiced otherwise than as specifically illustrated and described without departing from its spirit or scope.

WHAT IS CLAIMED IS:

1. A method for providing matching and introduction services to users of communications equipment comprising the steps of:
 - 5 storing at least two user profiles in a database;
 - storing the real-time geographic position of a plurality of users in said database;
 - a first user submits a first search request to a first server using a first wireless communications device;
 - 10 Said server performs a first search of said database;
 - said server returns search results to said first user;
 - facilitating communication between said first user and other users whose user profiles have been selected by said first user.
2. The method according to claim 1 wherein said user profiles are created and
15 stored using said wireless communications device.
3. The method of claim 1 or 2 wherein said user profiles are created and stored in said database via a World Wide Web connection.
4. The method of claim 1 wherein said first users current geographic position is determined by GPS technology integral to said wireless communications device.
- 20 5. The method of claim 1 wherein said first users current geographic position is determined by triangulation of radio waves emitted by said wireless communications device.
6. The method of claim 1 wherein said first users current geographic position is determined by Received Signal Strength Indication of the transmitted signal from said
25 wireless communications device by at least one receiving station remote from said communications device.
7. The method of claim 1 wherein said first users current geographic position is determined by said first user entering said position data via manual interface with said wireless communications device.
- 30 8. The method of claim 1 wherein said wireless communication device automatically determines and then transmits said first users current geographic position as part of said search request.

9. The method of claim 1 wherein said search of said database comprises the steps of:

initially sorting said user profiles based on geographic proximity to said first user;

5 further sorting the remaining said user profiles that contain at least one search_word specified by said first user;

finally selecting remaining user profiles that contain access control features that have been disabled.

10. The method of claim 9 wherein said search is performed a plurality of times in response to said user defining the periodicity and persistence of said search of said database.

11. The method of claim 9 wherein said first user is automatically notified if an additional user becomes proximate to said first user wherein said additional user meets criterion established in said search of said database.

15 12. A method of transmitting the geographic position of a wireless communications device in response to a user contacting a first display integral to said wireless device at a position on said display that correlates with said users current geographic position.

20 13. The method of claim 12 wherein the information presented on said display is a map, table of landmarks, or list of streets.

14. A method for providing matching and introduction services to mobile users of wireless communications equipment comprising the steps of:

creating and storing at least two user profiles in a database;

25 storing the real-time geographic position of a plurality of users in said database;

a first user submits a first search request to a first server using a first mobile wireless communications device;

said first users current geographic position is transmitted to said database with said search request;

30 a first search of said database is performed by said server using parameters provided by said first user;

said server returns search results to said first user;

facilitating communication between said first user and other users whose user profiles have been selected by said first user.

15. The method according to claim 14 wherein said user profiles are created and stored using said wireless communications device.
- 5 16. The method of claim 14 or 15 wherein said user profiles are created and stored in said database via a World Wide Web connection.
17. The method of claim 14 wherein said first users current geographic position is determined by GPS technology integral to said wireless communications device.
18. The method of claim 14 wherein said first users current geographic position is
10 determined by triangulation of radio waves emitted by said wireless communications device.
19. The method of claim 14 wherein said first users current geographic position is determined by Received Signal Strength Indication of the transmitted signal from said wireless communications device by at least one receiving station remote from said
15 communications device.
20. The method of claim 14 wherein said first users current geographic position is determined by said first user entering said position data via manual interface with said wireless communications device.
21. The method of claim 14 wherein said wireless communication device
20 automatically determines and then transmits said first users current geographic position as part of said search request
22. The method of claim 14 wherein said search of said database comprises the steps of:
 - updating said database with said first users current geographic position;
 - 25 initially sorting said user profiles based on geographic proximity to said first user;
 - further sorting the remaining said user profiles that contain at least one search_word specified by said first user;
 - finally selecting any remaining user profiles that contain access control
30 features that have been disabled.
23. The method of claim 22 wherein said search is performed a plurality of times in response to said user defining the periodicity and persistence of said search of said database.

24. The method of claim 22 wherein said first server automatically notifies said first user if additional users become proximate to said first user wherein said additional users meet criterion established in said search of said database.
25. The method of claim 22 wherein said search of said database further includes
- 5 the steps of syntax parsing and authenticating said first users search request.




FIG. 1




FIG. 2




FIG. 3

4/4




FIG. 4

SUBSTITUTE SHEET (RULE 26)

THIS PAGE BLANK (USPTO)

THIS PAGE BLANK (USPTO)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 May 2001 (10.05.2001)

PCT

(10) International Publication Number
WO 01/033429 A3

(51) International Patent Classification⁷: **G06F 17/30**

(21) International Application Number: PCT/US00/29516

(22) International Filing Date: 27 October 2000 (27.10.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/162,333 29 October 1999 (29.10.1999) US
09/691,322 18 October 2000 (18.10.2000) US

(71) Applicant: **GRAVITATE, INC.** [US/US]; 167 Hamilton Ave., Palo Alto, CA 94301 (US).

(72) Inventor: **TANAKA, Hirohisa, A.**; 350 Sharon Park Drive, Apartment 24 G, Menlo Park, CA 94025 (US).

(74) Agent: **ROSENFELD, Dov**; Inventek, 5507 College Avenue, Suite 2, Oakland, CA 94618 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,

DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:
20 November 2003

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR PROVIDING MATCHING AND INTRODUCTION SERVICES TO PROXIMATE MOBILE USERS AND SERVICE PROVIDERS

(57) Abstract: A system enabling mobile wireless users to obtain information on other proximate users both fixed and wireless. Said information is gathered from a central database that stores user profiles and real-time locations of system users. Mobile users can request information on nearby users by submitting a request from a mobile telephone or similar communications endpoint to the central database. The request is accompanied by the user's location, obtained from GPS (Global Positioning System) or other technology, or from user input. The server searches the profile database for nearby users based on requester's location, locations of other users of the system and optional parameters specified in the request. Search results are returned to the requester. The system facilitates communication between requester and owner(s) of profiles returned by system.

WO 01/033429 A3

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 00/29516

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G06F17/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y A	WO 99 33293 A (GLOBAL MOBILITY SYSTEMS) 1 July 1999 (1999-07-01) page 7, line 1 -page 15, line 20; figures	1-3, 8, 14-16, 21 4-7, 9-11, 17-20, 22-25
Y	WO 97 16934 A (JARLAB) 9 May 1997 (1997-05-09) page 11, line 27 -page 20, line 4; figures	1-3, 8, 14-16, 21
Y	WO 98 03025 A (MOTOROLA) 22 January 1998 (1998-01-22) page 3, line 5 -page 13, line 9; figures	12, 13
A Y	WO 97 14054 A (SNAPTRACK) 17 April 1997 (1997-04-17) page 4, line 25 -page 26, line 8; figures	1, 4 12, 13
	--- -/-- ---	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

15 September 2003

Date of mailing of the international search report

24/09/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Geoghegan, C

Int nal Application No
PCT/US 00/29516

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/29516

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9933293	A	01-07-1999	AU 1921799 A BR 9814503 A CA 2316386 A1 EP 1042933 A1 JP 2002517918 T WO 9933293 A1	12-07-1999 16-07-2002 01-07-1999 11-10-2000 18-06-2002 01-07-1999
WO 9716934	A	09-05-1997	SE 504186 C2 AU 7511796 A EP 0872129 A1 SE 9503843 A WO 9716934 A1	02-12-1996 22-05-1997 21-10-1998 02-12-1996 09-05-1997
WO 9803025	A	22-01-1998	US 5758264 A WO 9803025 A1	26-05-1998 22-01-1998
WO 9714054	A	17-04-1997	US 6131067 A AU 1131097 A US 6185427 B1 WO 9714054 A1 AU 7396096 A AU 7396596 A AU 7397396 A AU 7397596 A AU 723615 B2 AU 7662096 A BR 9611701 A CA 2230841 A1 CN 1199468 A CN 1211324 A , B DE 69625496 D1 DK 855041 T3 EP 1223434 A2 EP 1260830 A2 EP 0880713 A1 EP 0855041 A1 EP 0855039 A2 JP 11513787 T JP 11513788 T PT 855041 T US 2002084933 A1 WO 9714053 A1 WO 9714055 A1 WO 9714049 A2 WO 9714056 A1 WO 9714057 A1 US 6064336 A US 6259399 B1 US 6104340 A US 6016119 A US 6400314 B1 US 5874914 A US 5663734 A US 6133871 A US 2001028321 A1 US 5781156 A US 2002044087 A1	10-10-2000 30-04-1997 06-02-2001 17-04-1997 30-04-1997 30-04-1997 30-04-1997 30-04-1997 30-04-1997 31-08-2000 30-04-1997 28-12-1999 17-04-1997 18-11-1998 17-03-1999 30-01-2003 14-04-2003 17-07-2002 27-11-2002 02-12-1998 29-07-1998 29-07-1998 24-11-1999 24-11-1999 30-04-2003 04-07-2002 17-04-1997 17-04-1997 17-04-1997 17-04-1997 17-04-1997 16-05-2000 10-07-2001 15-08-2000 18-01-2000 04-06-2002 23-02-1999 02-09-1997 17-10-2000 11-10-2001 14-07-1998 18-04-2002

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 00/29516

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
WO 0019344	A	06-04-2000	AU	5882099 A		17-04-2000
			WO	0019344 A2		06-04-2000
WO 0115480	A	01-03-2001	US	6549768 B1		15-04-2003
			AU	6779100 A		19-03-2001
			EP	1212910 A1		12-06-2002
			WO	0115480 A1		01-03-2001
WO 0124551	A	05-04-2001	WO	0124551 A1		05-04-2001
			AU	5725599 A		30-04-2001
			EP	1169873 A1		09-01-2002
WO 0126408	A	12-04-2001	AU	7977200 A		10-05-2001
			EP	1243151 A1		25-09-2002
			WO	0126408 A1		12-04-2001
			SE	9903571 A		06-04-2001

THIS PAGE BLANK (USPTO)